

FIRE ALARM SYMBOLS

INDICATE HOW THE DEVICE IS MOUNTED (I.E. WALL, CEILING, ETC.)

SYMBOL	DESCRIPTION	NO. EA.	MODEL NO.
	HORN (OR SPEAKER) ONLY		
	HORN STROBE (SHOW CANDELA)		
	MINI HORN STROBE (SHOW CANDELA)		
	STROBE ONLY (SHOW CANDELA)		
	SMOKE DETECTOR—P (PHOTOELECTRIC) I (IONIZATION)		
	HEAT DETECTOR—R (RATE OF RISE) R/C (RATE COMP)		
	DUCT SMOKE DETECTOR		
	MAGNETIC DOOR HOLDER		
	MANUAL PULL STATION		
	DIGITAL ALARM COMMUNICATING TRANSMITTER		
	FIRE ALARM ANNUNCIATOR		
	FIRE ALARM CONTROL PANEL		
	WATERFLOW SWITCH		
	GAS DETECTOR		
	REMOTE INDICATOR		
	SUPPRESSION ABORT STATION		
	WATERFLOW EXTERIOR HORN/STOBE (WATERPROOF)		
	WATER VALVE WITH TAMPER		
	POST INDICATOR VALVE (PIV)		
	ILLUMINATED EXIST SIGN		
	FUSIBLE LINK		
	END-OF-LINE RESISTOR		
	DETECTION/EXT. EQUIP. — CA (CLEAN AGENT)		
OTHER SYMBOLS	REFER TO THE CURRENT EDITION OF NFPA 170 FOR PROJECT SPECIFIC OR OTHER SYMBOLS		